

Specification	IEC 60034-1	Efficiency class	IE1	
Manufacturer	AmTecs	Load data	100%	
Motor type	AMA 63 G4	Efficiency	56	%
Rated power	<b>0.18</b> kW <b>S1</b> Duty	Power factor	0.66	
Speed	<b>1340</b> rpm	Sound pressure level (1m)	41	dB(A)
Voltage	220V / 400V	Resistance R20 (open)		
Frequency	<b>50</b> Hz	Resistance R20 (Delta)		
Connection	Delta / Star			
Full load current	1.2 A / 0.7 A	Full load torque	1.28	Nm
No-load current		Starting / Full load torque	2.1	
Enclosure	IP55	Pull up / Full load torque		
Insulation class	F (temp. rise B)	Pull out / Full load torque	2.2	
Max. ambient temp	<b>40</b> °C			
Max. altitude	1000 mtr above sea level			
Comment				
Cable entry	M20 x 1.5	Starting / Full load current (DOL)	4.4	
Construction	Aluminium	Starting / Full load current (Y/D)		
Weight	<b>5.3</b> Kg	Rotor Inertia		
Type number		Bearing DE	6201	
Warranty		Bearing NDE	6201	

Electric Motors And Gearboxes Ltd
103 Morgan Close
Willenhall
West Midlands
WV12 4LH
01902 601403
sales@emag-ltd.co.uk