



Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMA-IE2 80 G2
Rated power 1.1 kW S1 Duty
Speed 2875 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 4.1 A / 2.37 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20x1.5
Construction Aluminium
Weight 13.5 Kg
Type number
Warranty

Efficiency class IE2
Load data 100%
Efficiency 79.6 %
Power factor 0.84
Sound pressure level (1m) 58 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)

Full load torque 3.65 Nm
Starting / Full load torque 3.2
Pull up / Full load torque
Pull out / Full load torque 3.8

Starting / Full load current (DOL) 7
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6204
Bearing NDE 6204

Electric Motors And Gearboxes Ltd
 103 Morgan Close
 Willenhall
 West Midlands
 WV12 4LH
 01902 601403
 sales@emag-ltd.co.uk



www.emag-ltd.co.uk