

Frame size	Rated output power	Rated current at			Full-load speed rpm	Full-load power factor	Full-load efficiency	Full-load torque	Starting current	Starting torque	Pull-out torque	Sound pressure level	Weight foot mounted
		230 V I <sub>L</sub> A	400 V I <sub>L</sub> A	690 V I <sub>L</sub> A									
AMA 71 K8	0.09	0.84	0.48		680	0.55	49	1.26	3.3	1.8	1.9	44	6.5
AMA 71 G8	0.12	1.10	0.63		690	0.55	50	1.66	3.3	1.8	1.9	44	7
AMA 80 K8	0.18	1.61	0.93		680	0.55	51	2.53	3.3	1.8	1.9	44	9.5
AMA 80 G8	0.25	1.91	1.10		680	0.61	54	3.51	3.3	1.8	1.9	44	11.5
AMA 90 S8	0.37	2.46	1.41		680	0.61	62	5.2	4	1.8	1.9	49	14.6
AMA 90 L8	0.55	3.59	2.07		700	0.61	63	7.5	4	1.8	2	49	17.6
AMA 100 L8	0.75	3.96	2.28		700	0.67	71	10.23	4	1.8	2	49	19.5
AMA 100 Lx8	1.10	5.48	3.15		710	0.69	73	14.80	5	1.8	2	49	21
AMA 112 M8	1.50	7.28	4.18		710	0.69	75	20.18	5	1.8	2	54	30
AMA 132 S8	2.20	9.97	5.73		720	0.71	78	29.18	6	1.8	2	58	51
AMA 132 M8	3.00	13.06	7.51		720	0.73	79	39.79	6	1.8	2	58	56
AMA 160 M8	4.00	16.8	9.7	5.6	720	0.73	81	53.1	6	2	2	59	60
AMA 160 Mx8	5.50		12.9	7.4	720	0.74	83	73.0	6	2	2	60	70
AMA 160 L8	7.50		16.8	9.7	720	0.75	85.5	99.5	6	2	2	60	87

EN60034-1(IEC-DIN)

230/400V -50Hz, 400/690v -50Hz

Detachable feet from size 56-160

Color Ral 5010

Information provided by  
**EMAG**  
 Tel: 01902 601403  
[www.emag-ltd.co.uk](http://www.emag-ltd.co.uk)