

Frame size	Rated output power	Rated current at	Full-load speed rpm	Full-load power factor	Full-load efficiency	Full-load torque	Starting current	Starting torque	Pull-out torque	Sound pressure level	Weight foot mounted
	P_N kW	230 V I_u A	n_N min^{-1}	$\cos \varphi$	100% η %	M_N	(A)	M_s/M_N	M_k/M_N	dB(A) 1 metre (no load)	kg
AMAS-SR 71K2	0.37	2.73	2800	0.92	67	0.129	16	2.3	1.8	72	7
AMAS-SR 71G2	0.55	3.88	2800	0.92	70	0.194	21	2.5	1.8	72	8
AMAS-SR 80K2	0.75	5.15	2800	0.92	72	0.260	30	2.5	1.8	75	8.5
AMAS-SR 80G2	1.10	7.02	2800	0.95	75	0.381	40	2.5	1.8	75	9.5
AMAS-SR 90S2	1.50	9.44	2800	0.95	76	0.522	55	2.5	1.8	78	12.5
AMAS-SR 90L2	2.20	13.67	2800	0.95	77	0.744	80	2.5	1.8	78	14
AMAS-SR 100L2	3.00	18.2	2800	0.95	79	1.044	110	2.5	1.8	91	20.5
AMAS-SR 112M2	3.70	22.85	2800	0.946	80	1.353	133	2.5	1.8	91	35
AMAS-SR 71K4	0.25	1.99	1400	0.92	62	0.174	12	2.5	1.8	67	6.9
AMAS-SR 71G4	0.37	2.81	1400	0.92	65	0.261	16	2.5	1.8	67	8.1
AMAS-SR 80K4	0.55	4.0	1400	0.92	68	0.383	21	2.5	1.8	70	8.9
AMAS-SR 80G4	0.75	5.22	1400	0.92	71	0.522	30	2.5	1.8	70	9.6
AMAS-SR 90S4	1.10	7.2	1400	0.95	73	0.766	40	2.5	1.8	73	13
AMAS-SR 90L4	1.50	9.57	1400	0.95	75	1.044	55	2.5	1.8	73	16
AMAS-SR 100L4	2.20	13.9	1400	0.95	76	1.531	60	2.5	1.8	86	23
AMAS-SR 100LX4	3.00	17.1	1400	0.96	78	2.088	70	2.5	1.8	86	30
AMAS-SR 112M4	3.70	22.01	1400	0.90	81	2.504	101	2.4	1.8	91	35

EN60034-1(IEC-DIN)

High starting & running torque, Centrifugal switch 230-50Hz ($M_a \Rightarrow 180\%$)

Detachable feet from size 56-112

Color Ral 5010

Information
provided by
EMAG
Tel: 01902 601403
www.emag-ltd.co.uk