



**BROOK  
CROMPTON**

## World Series Aluminium Range Frames 63 – 180

The W aluminium range offers products having outputs from as low as 0.07kW up to 22kW and available in frame sizes WU-DA63S to WU-DA180L.


They are used in a wide range of applications from food and drink to water and sewage, heating and ventilation, refrigeration and machinery.

Some of the benefits of aluminium over cast iron include high resistance to corrosion and atmospheric attack (except chlorine, salt-laden or sulphuric acid) and the fact that aluminium is approximately one third the weight of cast iron.

- 0.07kW – 22kW
- IE2 & IE3 Efficiencies
- IP55 - (Optional IP56, IP65, IP66)
- B3,B5,B35,B30,B14\*,B34\*(UPTO 160)
- Insulation Class F (Optional class H)
- Multimount Feet
- AC & DC Brake kit friendly (63-132)
- 2, 4, 6 & 8 Pole
- Steel Fan Cowl (Optional in Plastic on request)



IEC / BS  
Frame sizes  
63 - 180



NEMA  
Frame sizes  
56 - 286



IE2 or IE3  
Efficiency



UL  
Verified



IP55, IP56,  
IP65 or IP66

PLEASE SCAN FOR  
MORE INFORMATION:



*"Your Partner in Solutions"*